

ROTOGRAVURE PRESSES



**KOMORI
CHAMBON**




The many added value features available on the Mark Series rotogravure presses help you differentiate converted products on the shelf, enhance the brand image of your customers and at the same time produce consistent high quality in the most economical manner.

ROTOGRAVURE PRESSES



Product Features:


- ▲ **Reverse printing capacity** to get maximum differentiation
- ▲ **Electrostatic** printing assistance (ESA)
- ▲ **Low Explosion Level** control (LEL) for a safer production
- ▲ **Various** dryer capacities
- ▲ **Varnishes** & outstanding special effects
- ▲ **3D** doctor blade
- ▲ **Sleeve Impression** Roller
- ▲ **High precision printing** – Automatic adjustable compensator
- ▲ Many other options upon request



The full comprehensive integrated solutions we provide you with help you reach a top-printing quality at high speeds, increasing your effectiveness and reducing your production costs.

Modular designs, offering custom made presses, are possible thanks to a very stable mechanical base, responsible for the machines' sturdiness.

From roll to blank or roll to roll, we ensure an important reduction of waste thanks to the very efficient monitoring system (Supervisor). Our easily removable printing trolleys allow offline preparation and are the key to a flexible and user-friendly machine.



ROTOGRAVURE UNITS

Application Fields:

- ▲ **Tobacco**
- ▲ **Labels**
- ▲ **General Folding Boxes**
- ▲ **Other Packaging on demand**



GENERAL SPECIFICATIONS

MARK SERIES	MARK I - 26	MARK I - 32	MARK II - 32
Web flow	Right to left, printed side either up or down		
Web width	335 to 670 mm 12.7" to 26.3"	415 to 850 mm 16.3" to 33.5"	415 to 850 mm 16.3" to 33.5"
Print width	650mm 25.5"	830 mm 32.7"	830 mm 32.7"
Repeat range	400 to 800 mm 15.75" to 31.5"		
Substrate types	Paper, Paperboard or laminated paperboard		
Printing production speed	Up to 250 m/min Up to 820 ft/mn		Up to 350 m/min Up to 1150 ft/mn

	Front Printing	Reverse Printing
Accuracy print to print	+/- 0,10 mm +/- 0,004"	+/- 0,20 mm +/- 0,008"

FINISHING UNITS	DR 26	DR 32	DR 32
ROTARY DIE CUTTER			
Circumference range	580 to 1100 mm 22.8" to 43.3"	825 to 1650 mm 27.55" to 55.11"	825 to 1650 mm 27.55" to 55.11"
Substrate types	Paper, Paperboard or laminated paperboard		
Production speed	Up to 350 m/min (Up to 1150 ft/mn)		
PLATEN DIE CUTTER		Upon request	
REWINDER			
Production speed	Up to 350 m/min (1150 ft/mn)		Up to 350 m/min (1150 ft/mn)
LABEL CUTTER			
Label length	70 to 240 mm 2.75" to 9.4"	-	-
Label width	40 to 650 mm 1.57" to 25.59"	-	-
Substrate types	Paper, Paperboard or laminated paperboard	-	-
Production speed	Up to 180 m/min Up to 590 ft/mn	-	-

Converting Capacities:

Efficient in-line production of finished blanks by means of rotary or flatbed die-cutters, with stacker delivery

High speed, low waste operation of in-line sheeting, rewinding or label cutting.

Many added special effects for high added-value (e.g. different types of varnishes, hot foil, hologram)

www.komori-chambon.com



**KOMORI
CHAMBON**

KOMORI CHAMBON S.A.S.

13 bis avenue Buffon

CS26329 - 45063 ORLÉANS CEDEX 2 - FRANCE

Tél. 33 (0)238 645 500 - Fax. 33 (0)238 645 599